

The HFP H frame press is ideal for a whole variety of bending, forming, pressing, straightening and a whole variety of operations. The hydraulic system is equipped with a manometer and a joystick lever to control the operation. A pair of V blocks are supplied as standard equipment.

The H-Frame press range is an economical alternative to a press brake, highly versatile and capable of a wide range of jobs and tasks.



Machine Features

- Easily adjusted bed height with two hardened pins
- Bed designed to accept a variety of supports and jigs according to customer requirements
- Quiet hydraulic system
- Hydraulic cylinder mounted above providing vertical pressure
- Ideal for low or high volume operation.

Optional Equipment

- Digital Read Out
- Limit Switch
- Hand Pump
- Foot Pedal Control (instead of joystick)
- Foot Pedal Control with Limit Switch (instead of joystick)



JOYSTICK CONTROL



DIGITAL READ OUT (OPTIONAL)



FOOT PEDAL CONTROL (INSTEAD OF JOYSTICK) (OPTIONAL)



EASILY ADJUSTABLE BED HEIGHT



HAND PUMP (OPTIONAL)



HFP 775-30 AND HFP 1040-60



HYDRAULIC PRESSURE GUIDE & ADJUSTMENT

WATCH THE MACHINE IN ACTION



TECHNICAL SPECIFICATIONS

MODEL	Stock Code	Power	Distance between Frames	Stroke	Advance Speed	Working Speed	Return Speed	Motor Power	Length	Width	Height	Weight
		Tonnes	mm	mm	mm/sec	mm/sec	mm/sec	kW	mm	mm	mm	kg
HFP 775/30	M4500	30	775	200	8	5	10	3	1500	700	1800	410
HFP 1040/60	M4501	60	1040	250	8	4	10	4	1850	700	2100	790
HFP 1070/100	M4502	100	1070	300	8	5	10	5.5	2050	1000	2200	1520
HFP 1570/100	M4503	100	1570	300	9	5	10	5.5	2500	1000	2200	1900
HFP 1070/150	M4504	150	1070	300	9	5	10	11	2050	1000	2270	1620
HFP 1570/150	M4505	150	1570	300	9	5	10	11	2500	1000	2270	2150