

01432 346 580

Sterling
Twin Column Single Mitring
Semi Automatic Bandsaws

Metalworking
 Solutions
 Supplied

BANDSAWS



Machine Features

- Strong twin pillar frame with linear guidance bearing.
- Mitring swivel head to 60°.
- Hydraulic cutting with variable pressure and variable speed.
- Hydraulic vice.
- Hydraulic bow lock at any angle.
- Digital readout for mitre angle.
- Variable blade speed 20-100 m/min.
- Carbide blade guides.
- Blade tension indicator.

Optional Equipment

- Hydraulic blade tension.
- Hydraulic top clamps.
- Chip conveyor.
- Spray mist lubrication.
- Laser cutting line.



SENSITIVE CUTTING PRESSURE



TECHNICAL SPECIFICATIONS

MODEL	STC325 GSA			STC360 GSA			STC440 GSA			STC540 GSA			STC810 GSA		
Capacity	90°	45° R	60° R	90	45	60	90°	45° R	60° R	90°	45° R	60° R	90°	45° R	60° R
○ mm	325	305	190	360	360	305	440	440	305	540	510	270	810	530	320
□ mm	320	270	180	360	360	305	440	440	305	540	455	240	770	520	320
▭ mm	450x320	270x320	180x240	700x360	460x360	305x360	700x440	460x440	305x440	750x540	455x540	240x540	810x770	500x750	310x750
Blade Size	mm 4160 x 34 x 1.1			5000x34x1.1			5200 x 41 x 1.3			6000 x 41 x 1.3			8200 x 41 x 1.3		
Cutting Speed	m/min 20 - 100			20-100			20 - 100			20 - 100			20 - 100		
Motor	Kw 2.2			3			4			4			4		
Length	mm 2100			2850			2850			2900			3940		
Width	mm 800			2100			780			1100			1300		
Height	mm 1600			1910			2125			2130			2470		
Weight	Kg 1150			1550			1630			2100			3100		
Operation	Semi-Automatic			Semi-Automatic			Semi-Automatic			Semi-Automatic			Semi-Automatic		
Vice	Hydraulic			Hydraulic			Hydraulic			Hydraulic			Hydraulic		