

The comprehensive Sterling range starts with the compact but robustly constructed SRA230 DG model. This machine features auto downfeed operation with variable cutting pressure. The double mitring head design allows the cutting of angles to either the left or the right without turning the material over. It is also available as a semi-automatic variant - the SRA230 DGSA - which has in addition a hydraulic vice and automatic bow return. Two blade speeds are standard on either model, suitable for cutting either mild or stainless steel.

## Machine Features

- Auto downfeed with variable cutting pressure
- Double mitring swivel head 45° left and 60° right
- Quick release manual vice
- Vice slides from left to right
- Carbide blade guides for high accuracy
- Two cutting speeds
- Coolant system
- Safety interlock switches fitted to band cover

### ADDITIONAL FEATURES SRA230 DGSA

- Hydraulic vice
- Automatic bow return with height adjustment

## Optional Equipment

- Roller track and measuring systems



SRA230 DG

## TECHNICAL SPECIFICATIONS

MODEL STOCK CODE	SRA230 DG 15140				SRA230 DGSA 15199			
	90°	45° L	45° R	60° R	90°	45° L	45° R	60° R
Capacity	90°	45° L	45° R	60° R	90°	45° L	45° R	60° R
○ mm	230	220	180	120	230	220	180	120
□ mm	230	190	150	105	230	190	150	105
▭ mm	320 x 130	230 x 140	220 x 60	120 x 105	320 x 130	230 x 140	220 x 60	120 x 105
Bed Height	mm 760				mm 760			
Blade Size	mm 2730 x 27 x 0.9				mm 2730 x 27 x 0.9			
Cutting Speed	m/min 35/70				m/min 35/70			
Motor	Kw 1.0/1.5				Kw 1.0/1.5			
Length	mm 1350				mm 1350			
Width	mm 900				mm 900			
Height	mm 1300				mm 1300			
Weight	Kg 345				Kg 465			
Operation	Auto down feed				Semi-automatic			
Vice	Manual				Hydraulic			